

Product Description

D-A HydraTrans™ LV is a proven premium grade transmission and hydraulic fluid providing superior performance for severe service off-highway applications. It is formulated from high-quality base stocks fortified with a high-performance additive system to extend component life and improve performance characteristics. D-A HydraTrans LV supports the performance requirements for most major agricultural equipment manufacturers, allowing users to stock one fluid to meet both transmission and hydraulic system needs. D-A HydraTrans LV is a lower viscosity tractor fluid designed for service in

Product Features and Benefits

- Improves hydraulic pump and gear train life to help reduce maintenance costs.
- Improved oxidation stability extends oil life.
- Improved frictional properties prevent grabbing or chattering of wet brakes and PTO clutches.
- Excellent water tolerance and low temperature fluidity provides protection in all working environments.
- Provides rust and corrosion protection for all types of metal surfaces, increasing component life.
- Supports the performance requirements of both hydraulic and transmission field service for major construction and agricultural equipment manufacturers reducing the need to inventory separate lubricants.

PRODUCT AT A GLANCE

- Lower Viscosity Tractor Fluid
- Transmission and Hydraulic Fluid
- Designed for use in Severe Service
- Longer Pump Life
- Good for use in Cold Weather



D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065 • EMAIL: dalube@dalube.com
www.dalube.com



Typical Applications - Supports the Performance Requirements of:

Case New Holland - FNHA-2-C-201.00
John Deere - J20B & J20D

Typical Properties

API Service Classification (meets specifications)		GL-4
Viscosity		
@ 100°C, cSt	ASTM D445	6.9
@ 40°C, cSt	ASTM D445	31.5
@ -20°C, cP	ASTM D5293	1,200
@ -25°C, cP	ASTM D5293	1,900
@ -30°C, cP	ASTM D4684	4,000
@ -40°C, cP	ASTM D2983	17,000
Viscosity Index	ASTM D2270	188
Flash Point,		
°F	ASTM D92	410
°C	ASTM D92	210
API Gravity	ASTM D287	33.7
Humidity Cabinet Rust Test, Hours		200+
Vickers Pump Test		PASS
Tractor Performance Tests		
Transmission Durability		PASS
Gear Wear Protection		PASS
Brake Chatter and Capacity		PASS
Power Take Off Clutch		PASS
D-A Part Numbers:		
	Bulk	57521
	Drum, 55 Gal	57522
	Pail, 5 Gal	57528

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823) or Fax orders to 765-482-3065

D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065

Email: dalube@dalube.com • www.dalube.com

