

### Product Description

D-A evolve<sup>™</sup> tractor fluid is a proven premium grade transmission and hydraulic fluid providing superior performance for severe service off-highway applications. It is formulated from high-quality re-refined and virgin base stocks fortified with a high-performance additive system to extend component life and improve performance characteristics. D-A evolve<sup>™</sup> tractor fluid meets the specifications of most major agricultural equipment manufacturers, allowing users to stock one fluid to meet both transmission and hydraulic system needs.

### Product Features and Benefits

Improves hydraulic pump and gear train life to help reduce maintenance costs.  
Improved oxidation stability extends oil life.  
Improved frictional properties prevent grabbing or chattering of wet brakes and PTO clutches.  
Excellent water tolerance and low temperature fluidity provides protection in all working environments.  
Provides rust and corrosion protection for all types of metal surfaces, increasing component life.  
Complies with hydraulic and transmission field service requirements of major agricultural equipment manufacturers reducing the need to inventory separate lubricants.

### PRODUCT AT A GLANCE

- Premium Grade Tractor Fluid
- Transmission and Hydraulic Fluid
- Designed for use in Severe Service
- Meets requirements of most major agricultural manufacturers
- Good for use in Cold Weather



D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065 • EMAIL: dalube@dalube.com  
www.dalube.com



## Typical Applications

John Deere — JDM JC20A & JC20C  
 Ford New Holland — FNHA-2-C-201.00; ESN-M2C134 A, B, C & D; ESN-M2C86B  
 Massey-Ferguson — M-1141; M-1135; M-1129-A; M-1127-A&B; M-1110  
 Case — MS-1207; MS-1210/JIC-145; MS-1204/JIC-185; MS-1230  
 Kubota — UDT  
 White Farm — Q-1826 HTF  
 Agco/Deutz-Allis — Power Fluid 821XL  
 Allison — C-3 and C-4  
 Volvo — WB101

## Typical Properties

Kinematic Viscosity		
@ 100°C, cSt	ASTM D445	9.5
@ 40°C, cSt	ASTM D445	61.8
Brookfield Viscosity		
@ -18°C, cP	ASTM D5293	3,720
@ -20°C, cP	ASTM D5293	4,500
@ -29°C, cP	ASTM D4684	19,200
@ -35°C, cP	ASTM D2983	57,000
Viscosity Index	ASTM D2270	140
Flash Point,		
°F	ASTM D92	425
°C	ASTM D92	218
API Gravity	ASTM D287	28.0
Humidity Cabinet Rust Test, Hours		200+
Vickers Pump Test		PASS
Tractor Performance Tests		
Transmission Durability		PASS
Gear Wear Protection		PASS
Brake Chatter and Capacity		PASS
Power Take Off Clutch		PASS
	Bulk	57551

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823) or Fax orders to 765-482-3065

**D-A Lubricant Company, Inc.**

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065

Email: [dalube@dalube.com](mailto:dalube@dalube.com) • [www.dalube.com](http://www.dalube.com)

