

Product Description

D-A Cross Transformer Oil is a specially processed, inhibited, naphthenic transformer oil that meets ASTM D3487 transformer oil requirements.

It contains no harmful polychlorinated biphenyls (PCB's) or corrosive sulfur. Its low moisture content ensures high electrical resistance, and both thermal and oxidative stability. D-A Cross Transformer Oil is highly stable and not corrosive to copper. Its low pour point and low viscosity provides excellent heat transfer under all temperature conditions. The high flash point provides for a margin of safety.

Product Features and Benefits

- Prolonged transformer life - excellent heat transfer properties improve cooling of transformer components.
- Maximized life of oil immersed switches - Rapid quenching of arcs reduces contact erosion.
- Transformer efficiency - High dielectric strength and low dissipation factor provides excellent insulating characteristics.
- Extended service life - Oxidation stability of D-A Cross Transformer Oil limits the formation of sludge, deposits and soluble compounds which break down the electrical properties of the oil in extended service conditions.

PRODUCT AT A GLANCE

- Naphthenic transformer oil
- Meets ASTM D3487
- No PCBs
- Highly stable
- Low pour point
- High flash point



D-A Lubricant Company, Inc.



Typical Applications

D-A Transformer Oil is recommended for use in arc-forming apparatus including:

- Oil immersed transformers
- Switches
- Circuit breakers
- Oil-filled capacitors
- Tap changers
- Electrical enclosures
- Fuses

D-A Transformer Oil complies fully with the following Specifications:

- ASTM D-3487, Type II
- Doble TOPS-884, Inhibited Type II
- BS 148:1984, Class IIA (Inhibited)
- IEC 296:1982, Class IIA (Inhibited)
- CAN/CSA-C50-97, Type II (Class B)

Typical Properties

Viscosity, cSt @

@ 100°C	ASTM D445	2.34
@ 40°C	ASTM D445	9.54
Pour Point °C (°F)	ASTM D97	-54 (-65.2)
Flash Point °C (°F)	ASTM D92	150 (302)
Specific Gravity, 15°C/60°F	ASTM D1298	0.894
Dielectric Breakdown Voltage		
60 Hz: Disc electrodes, KV	ASTM D877	50
Power Factor @ 60 Hz, % max		
@ 100°C	ASTM D924	0.05
PCB Content, ppm	ASTM D4059	None Detected

Available by special order only. Please contact D-A regarding pricing, minimum order quantity and lead time.

D-A Part Number	Drum, 55 Gal	57012
-----------------	--------------	-------

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823) or Fax orders to 765-482-3065

D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065

Email: dalube@dalube.com •

