

# Turbine Oil SG



---

## Product Description

D-A Turbine Oil SG is a custom-blended polyalphaolefin (PAO) synthetic hydrocarbon fluid giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

D-A Turbine Oil SG is a long life lubricant formulated with rust, oxidation and wear inhibitors. Other viscosities are available for specific applications.

USDA approved for use in federally inspected meat and poultry plants with no possibility of food contact (H-2).

---

## Product Features and Benefits

Low temperature fluidity for low-torque start-up *reduces component wear.*

Formulated from premium quality synthetic base oils and additives *for super oxidation and thermal stability, resisting varnish and coke deposits.*

Exceptional oxidation stability *promotes extended drain intervals and reduced maintenance costs.*

Synthetic base oil is *compatible with seals and elastomers commonly found in steam and gas turbines.*

# Turbine Oil SG



---

## Service Applications

### Steam and Gas Turbine Applications

USDA approved for use in federally inspected meat and poultry plants with no possibility of food contact (H-2)

---

#### Typical Properties:

<b>ISO Viscosity Grade</b>	<b>32</b>
<b>Viscosity, cSt @</b>	
@ 100°C	5.97
@ 40°C	30.72
<b>Viscosity Index</b>	<b>144</b>
<b>Pour Point, °F (°C)</b>	<b>-90 (-68)</b>
<b>Flash Point, °F (°C)</b>	<b>470 (243)</b>
<b>Fire Point, °F (°C)</b>	<b>520 (271)</b>
<b>Specific Gravity</b>	<b>0.835</b>
<b>Density, lb/gal 60 °F</b>	<b>6.95</b>

**To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823)  
Or Fax orders to (317) 923-3884**

**D-A Lubricant Company, Inc.  
1340 W. 29th Street, Indianapolis, IN 46208 (317) 923-5321 • (317) 923-3884 FAX  
www.dalube.com • dalube@dalube.com**