

WearGuard™ SYN Hi-Temp Chain Oil is 100% synthetic chain oil based on neopolyol esters and innovative anti-oxidant. This product is blended with D-A's advanced ChemGuard™ additive technology to enhance antiwear properties and give a very high resistance to thermo-oxidation and coking. The choice of a highly oxidation stable ester with innovative anti-oxidants gives the oil an outstanding resistance to oxidation and coking.

WearGuard™ SYN Hi-Temp Chain Oil is recommended for high temperature applications, up to 482-572°F and even higher peak temperature, like chains for glass mills, cement industry, etc...This product is also acceptable as a lubricant where there is no possibility of food contact (H2) in and around food processing areas.

Characteristics

- Excellent antiwear properties
- Outstanding resistance to coking
- Low volatility
- High Flash Point

Typical Properties

WearGuard™ D-A SYN HTC Series	ASTM Test	WearGuard™ D-A HTC 150	WearGuard™ D-A HTC 220
ISO Viscosity	D2422	150	220
Appearance	n/a	Amber	Amber
Odor	n/a	Mild	Mild
Viscosity, cSt			
40°C	D445	150	220
100°C	D445	13	20
Viscosity Index	D2270	83	86
Flash Point, °F/°C, (COC)	D92	514/268	552/289
Fire Point, °F/°C, (COC)	D92	536/280	572/300



801 Edwards Drive Lebanon, IN 46052
1-800-OIL-LUBE (1-800-645-5823)
(317) 923-5321 (765) 482-3065 FAX
www.dalube.com dalube@dalube.com

DA-SYNHTC rev 5/2013

The information in this bulletin is, to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

© 2013, D-A Lubricant Company, Inc.